

ROTATHENE® 10UV

LLDPE Rotational Moulding Resin

Description

Rotathene® 10UV is a Hexene co-polymer based Linear Low Density Polyethylene resin (LLDPE) specifically designed for rotational moulding applications. It has good ESCR and excellent toughness.

Rotathene® 10UV is a general purpose LLDPE resin intended for applications requiring a high level of surface detail as well as low shrinkage and warpage. It contains a high level of UV stabiliser to give protection for outdoor use. Rotathene® 10UV is available in the full range of Rotathene® colours. A colour matching service is also available upon request.

When used in accordance with FDA application guidelines, Rotathene® 10UV** conforms to the requirements of U.S. FDA 21 CFR 177.1520 (c) 3.1a and AS2070-1999 sec.4.1.1 (a). Containing UV stabilisation, the conditions described in FDA 21 CFR 176.170 (c) table 2, conditions B to H apply. Volume, temperature and food type restrictions may apply. This product should not be used in applications for holding food during cooking without the required product compliance testing.

Typical Applications

Display Applications
Toys and complex custom mouldings

General Purpose Custom Moulding
Outdoor Applications

Properties ***	Unit	Value	Test Method
MFI ^(2.16/190)	g/10min	10	ASTM D1238
Density	g/cm ³	0.930	ASTM D1505
ESCR ² (F ₅₀)	hours	700	ASTM D1693
Flexural Modulus (Youngs)	MPa	408	ASTM D760M
Tensile Strength @ Yield ¹	MPa	15	ASTM D638
Tensile Strength @ Break ¹	MPa	11	ASTM D638
Elongation @ Break ¹	%	470	ASTM D638M
Notched Izod Impact @-40°C	J/m	178	ASTM D256
Durometer Hardness	Shore D	52	ASTM D2240
Vicat Softening Temperature	°C	109	ASTMD1525
Heat Deflection Temp	@455kPa °C	68	ASTM D648
	@1820kPa °C	34	

*** Base Resin – Properties

- 50 mm/min
- 100% Antarox solution

Test data as stated by Raw Material Manufacturer datasheets and brochures - as measured on virgin natural resin.

Typical (average) Values only – not to be considered as specifications

** Rotathene® 10UV natural and tanks colours – for FDA status on all other colours please contact your local Vanglobe representative.

Vanglobe Pty Ltd
ABN 64 010 842 243

Brisbane (Head Office) 37 Antimony Street, PO Box 104, Carole Park QLD 4300 Australia
Perth 559 Valencia Way, Maddington WA 6109 Australia
Melbourne

T 61 7 3271 3955 T/F 1800 888 141 F 61 7 3271 4532
T 61 8 9493 6414 F 61 8 9493 6416
T 61 3 8361 8838 F 61 3 8361 8445
E sales@vanglobe.com.au support@vanglobe.com.au

Vanglobe New Zealand Pty Ltd
ACN 113 712 557

Auckland (Head Office) 44-46 Princes Street, PO Box 13966, Onehunga, Auckland

T 64 9 634 5334 T/F 0800 56 33 56 F 64 9 634 5335
E customerservices@vanglobe.co.nz
support@vanglobe.com.au

Important Information

Before using this product, moulders are advised to conduct their own determination of the safety and suitability of the product for their specific application and is further advised against relying on the information contained herein as it may relate to any specific use or application. Whilst all care is taken in the preparation of this information, Vanglobe Pty Ltd/ Vanglobe New Zealand Pty Ltd and its employees cannot be held responsible for the subsequent use of this information by any third party. The properties quoted are based on standard test methods and standard moulded plaques and shapes. It is essential that you ensure the suitability of the material for your specific application prior to use. It is the ultimate responsibility of the user to ensure this product is suited for, and the information is applicable to the user's specific application.

Combustibility

Polyethylene will burn when supplied with sufficient heat and oxygen. They should be handled and stored away from contact with direct flames and/or other ignition sources. Polyethylene resins will contribute high heat and may generate a dense black smoke whilst burning. Conventional fire fighting means may be used to extinguish Polyethylene fires, with water and water mist being preferred. Fire Fighters should be provided with self contained breathing apparatus when operating in enclosed areas

Explosion Hazard

While care is taken to keep the amount of sub 150µm particles to a minimum, some fines will always be present in the powder. These fines can, under certain conditions, pose an explosion hazard. We recommend that the processing equipment has adequate grounding at all times and good housekeeping be practiced throughout the facility.

Storage/Handling

Rotathene® resins should be stored in a clean, dry place at ambient temperatures. Prolonged or improper storage can result in deterioration of product properties. Care should be taken when handling and transferring product to prevent foreign matter contamination.

Contact

For further information on Rotathene®, please contact the Vanglobe office closest to you. Vanglobe Technical can be contacted at Vanglobe Melbourne or by emailing support@vanglobe.com.au.

G:\Knowledge Management Centre\Technical Data Sheets\February 2006\Rotathene\Rotathene 10UV Technical Data Sheet 0206V1 website .doc

Vanglobe Pty Ltd ABN 64 010 842 243

Brisbane (Head Office)	37 Antimony Street, PO Box 104, Carole Park QLD 4300 Australia	T 61 7 3271 3955	T/F 1800 888 141	F 61 7 3271 4532
Perth	559 Valencia Way, Maddington WA 6109 Australia	T 61 8 9493 6414	F 61 8 9493 6416	
Melbourne		T 61 3 8361 8838	F 61 3 8361 8445	
		E sales@vanglobe.com.au support@vanglobe.com.au		

Vanglobe New Zealand Pty Ltd ACN 113 712 557

Auckland (Head Office)	44-46 Princes Street, PO Box 13966, Onehunga, Auckland	T 64 9 634 5334	T/F 0800 56 33 56	F 64 9 634 5335
		E customerservices@vanglobe.co.nz support@vanglobe.com.au		